



NOTES:

1. LATERAL CLEANOUT SHALL BE PLACED ON PRIVATE PROPERTY UNLESS AUTHORIZED BY AN ENCROACHMENT PERMIT FROM THE DEPARTMENT OF PUBLIC WORKS. MAINTENANCE OF THE CLEANOUT IS THE RESPONSIBILITY OF THE PROPERTY OWNER.
2. FOR NEW SEWER INSTALLATIONS, ONCE THE NEW SEWER MAIN AND LATERALS HAVE BEEN TESTED, ACCEPTED AND APPROVED TO BE PUT ON-LINE, CONTRACTOR SHALL CONNECT THE BUILDING LATERAL TO THE NEW CLEANOUT.
3. WHERE LATERAL CLEANOUT IS LOCATED IN DRIVEWAYS OR OTHER AREAS SUBJECT TO VEHICULAR TRAFFIC, INSTALL A 4' THICK BY 24" SQUARE CAST CONCRETE BLOCK WITH APPROPRIATE DIAMETER HOLE IN CENTER OVER CLEANOUT PIPE AS SHOWN.
4. TWO-WAY CLEANOUT FITTING SHALL BE OF A TYPE THAT IS LISTED AND APPROVED BY AN ACCEPTABLE LISTING AGENCY.
5. CLEANOUT SHALL BE FITTED WITH AN APPROVED BACKWATER VALVE WHEN REQUIRED BY THE CALIFORNIA PLUMBING CODE (WHEN PROPERTY SERVED BY THE LATERAL HAS, OR WILL HAVE FIXTURES WITH FLOOD LEVEL RIMS BELOW THE NEXT UPSTREAM MANHOLE.) MAINTENANCE OF BACKWATER VALVE IS THE RESPONSIBILITY OF THE PROPERTY OWNER.

DWG DATE 5-07		SCALE NTS	CITY OF YREKA • DEPARTMENT OF PUBLIC WORKS	
			APPROVED BY <i>Steven D. Neill</i>	TWO WAY CLEANOUT CONNECTION
MARK	DATE	REVISION	STEVEN D. NEILL, P.E. RCE #33385 DIRECTOR OF PUBLIC WORKS	